

Our products / Protection against direct effects of lightning

> Brackets and fixings >

■ The extended masts

These 304L stainless steel extended masts are used to raise the height of the Air Terminal on the highest point of the building.

[They can be lengthened depending on the height required

[Delivered with fixation collar in stainless steel at the bottom part.

[The masts are simply inserted and the stainless steel bolt screwed on the nut.

• 11037/11039/11041



| Ref | Designation | Material | Length | Diamètre extérieur | Weight |
|-------|-----------------------|-----------|--------|--------------------|--------|
| 11037 | 1 ^{er} mast | S/s 304 L | 2 m | 33,7 mm | 3 kg |
| 11039 | 2 ^{ème} mast | S/s 304 L | 2 m | 42,4 mm | 6 kg |
| 11041 | 3 ^{ème} mast | S/s 304 L | 2 m | 48,3 mm | 7 kg |

Their installations by superimposition on a 200 mm retraits with tightening by 304L stainless steel ring allows to reach the heights of:

Global set : 11037 = 2,03 m

Global set : 11037 + 11039 = 3,65 m

Global set : 11037 + 11039 + 11041 = 5,35 m

For greater height : Please consult us.

*Maximum height admitted : 8 m (guy wire needed).

For any height up than 8m : Installer's responsibility.

Ref. 11037/11039/11041

