

## TECHNICAL DATASHEET



### SPECIFICATIONS

Reference	11055
Designation	FPIC® isolated mounting mast with adapter and clamping ring
Guarantee	1 year
Material	Polyoxymethylene (POM)
Length	1.20 m
Ext. Diam.	50 mm
Int. Diam.	36.0 mm

### APPLICATION

Our **FPIC®** isolated mounting mast enables ESE air terminals from the **IONIFLASH MACH® NG** range installed in an **FPIC®** isolated system to be securely fixed. If a metal pole is used, the lightning protection system can no longer be considered isolated because the lightning current could pass through it.



The **FPIC®** can be routed inside the isolated mast.



Up to 4 **FPIC®** can be connected to the mast.

### PARTS INCLUDED

FPIC® isolated mounting mast in POM	Length 1.20 m Thread for adapter mounting
304L stainless steel mounting adapter	Allows the ESEAT to be fixed to the mast and connected to up to 4 isolated conductors
304L stainless steel clamping ring	Holds the isolated mounting mast securely in place on the mounting system used.

### FPIC® ISOLATED MAST EXTENSIONS

To reach a mast height of over 1.20 m, use the **FPIC®** extension mast (ref. 11058). Several masts can be nested together to reach the required height.

**Qualifoudre**  
INERIS  
N° 051168729019



COMPLIES WITH  
IEC TS 62561-8  
EUROCODE 1

 **La FRENCH FAB**