

EARTH ROD

TECHNICAL DATASHEET

SPECIFICATIONS

	16108 - 16105 - 16106
Description	Earth rod ø 15 mm
Material	304L stainless steel
Ref. 16108	L. = 1.0 m / W. = 1.35 kg / ø = 15 mm
	L. = 1.5 m / W. = 2.02 kg / ø = 15 mm
Ref. 16106	L. = 2.0 m / W. = 2.70 kg / ø = 15 mm

USING

Principle	This product can be used as a vertical electrode in a lightning earthing system.	
Additional accessories	Coupling sleeve - Ref. 16113 To be used to connect two earth rods	
	Hammer tip - Ref. 16133 To be used to hammer earth rods without damages	0

CONNECTION









contact@france-paratonnerres.com https//france-paratonnerres.com/en/ +33 5 55 57 52 53



Ref. 16127 Stainless steel fixing ring For flat conductors



Ref. 16125 Copper connecting collar For flat conductors

COMPLIANCE

IEC 62561-2

Components for lightning protection systems (CSPF) - Part 2: Requirements for conductors and grounding electrodes

Ref. 16121

Brass fixing ring

For round conductors

As part of our process of innovation and improvement, we reserve the right to make changes to shape, features and dimensions without prior notice. Illustrations are therefore non-binding.